



SMART
LAUNDRY
TECHNOLOGY



Stacked Washer and Dryer

MODEL

FTEE5A

WASHER 8KGS

DRYER 8KGS



DIMENSIONS & SPECIFICATIONS

MODEL	FTEE5A
AVAILABLE CONTROL	ELECTRONIC
AVAILABLE CONTROL LOCATION	FRONT
CAPACITY KG (LB)	UPTO 8KG (BOTH WASHER AND DRYER)
CYLINDER VOLUME LITERS (CU.FT)	198 (7.0)
WIDTH MM (IN)	683 (26 7/8)
DEPTH MM (IN)	704 (27 3/4)
HEIGHT MM (IN)	1986 (78 3/16)
SPIN SPEED G-FORCE (RPM)	N/A
MOTOR SIZE KW (HP)	0.25 (1/3)
WATER CONSUMPTION PER CYCLE (G)	N/A
AVAILABLE HEAT SOURCES	ELECTRIC
AVAILABLE HEATING ELEMENT (ELECTRIC W)	(AUSTRALIA) 4000 @ 230V, (CANADA) 4250@ 208V, 4750@208V, 4800 @ 230V, 5000 @ 240V, 5000@ 400V (EXCEPT STACK DRYER /DRYER), 5350@ 240V
GAS INLET CONNECTION MM (IN)	-----
GAS CONSUMPTION BTU/HR	-----
EXHAUST OUTLET DIA .MM (IN)	102 (4)
EXHAUST AIRFLOW LITRES/SEC (CFM)	85 (180)
AVAILABLE WATER TEMPRATURES	N/A
AVAILABLE CYCLES	REGULAR, PERM PRESS, DELICATE, TIME DRY, QUICK DRY, FLUFF UP
WATER PRESSURE BAR (PSI)	N/A
CYCLE INDICATOR LIGHTS	YES
CYLINDER FINISH	GALVANIZED
AVAILABLE COLORS	WHITE
DOOR TYPE (SOLID/WINDOW)	WINDOW
AVAILABLE ELECTRICAL REQUIREMENTS (VOLTAGE/HZ/PH)	ELECTRIC: 120/208/60/1 - 30 AMP, ELECTRIC: 220/60/1 - 30 AMP, ELECTRIC: 230/50/1 - 30 AMP.
NET WEIGHT KG (LB)	177 (390)
SHIPPING WEIGHT KG (LB)	193 (425)
SHIPPING DIMENTIONS	
WIDTH MM (IN)	737 (29)
DEPTH MM (IN)	832 (32 3/4)
HEIGHT MM (IN)	2032 (80)